

**E26****G40****OPAL IVORY LED 100W EQUIVALENT**

H 6½"

Ø 4<sup>7</sup>/<sub>8</sub>"**PACKAGING**

NOTE: Refer to image for scale/Se référer à l'image pour l'échelle

**SPECIFICATIONS**

WATTS	10
DELIVERED LUMENS	950
LAMP SHAPE	G40
GLASS SHADE	OPAL*
BASE / ANSI BASE	MEDIUM / E26
MAXIMUM HEIGHT	6½"
MAXIMUM DIAMETER	4 <sup>7</sup> / <sub>8</sub> "
CRI	80+
BEAM ANGLE	360°
JAB CERTIFIED	NO
ENCLOSED RATED	YES
OPERATING TEMP.	-20° C TO 45° C
CASE QUANTITY	12/36
LIFE CYCLE @ 3 HRS/DAY	23 YEARS
ENERGY COST @10.65¢/kWh†	\$0.82 / YEAR
WARRANTY	3 YRS / 20,000 HRS

† Refers to Estimated annual cost



DESCRIPTION	ACTIVE CODE	SCHEDULED SKU UPDATE	SCHEDULED NEW CODE
● 3000 KELVIN · LUMENS 950	<b>DG4030WP10A</b>		

\*Opal/Frosted bulb SKUs may exhibit warmer colour temperatures than their Clear-glass counterparts and cannot be directly compared due to glass differences.

**DIMMABILITY DATA / DONNÉES DE GRADATION**

- ✓ SMOOTH AND CONSISTENT DIMMING
- X NOT RECOMMENDED
- INCONSISTENT DIMMING TRANSITION
- ^ POTENTIAL STROBING AT THIS LEVEL
- MIN LOSES DIMMABILITY BELOW THIS LEVEL
- MAX MAXIMUM LUMENS OUTPUT

\*This chart is for D462x8A series only - for DVLG40MTxxA charts, please flip to Page 82 for superceded data

	2 BULBS					5 BULBS					30 BULBS							
	MIN	20	40	60	80	MAX	MIN	20	40	60	80	MAX	MIN	20	40	60	80	MAX
LEGRAND ADORNE SOFTAP ADTP703U	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
LUTRON MAESTRO MACL-153MH		MIN	✓	✓	✓	✓		MIN	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
LUTRON DIVA® / DIVA® C.L DVWCL-153PH	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
LEVITON DECORA SURESLIDE®	✓	MIN	✓	✓	✓	✓		MIN	✓	✓	✓	✓		MIN	✓	✓	✓	✓
LUTRON C.L SKYLARK CONTOUR CTL -153P	✓	✓	✓	✓	✓	^	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
LUTRON CASETA® WIRELESS	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
LEVITON DECORA ROCKER SLIDE	✓	MIN	✓	✓	✓	✓		MIN	✓	✓	✓	✓		MIN	✓	✓	✓	✓
LEVITON DECORA SMART™	✓	MIN	✓	✓	✓	✓		MIN	✓	✓	✓	✓		MIN	✓	✓	✓	✓
LUTRON MAESTRO PRO MA-PRO-WH	✓	✓	✓	^	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓