DVI®

WWW.DVI.LIGHTING

DAWSON

ASSEMBLY INSTRUCTIONS

DVP44138
DVP44148

Warning
All electrical connections must be made according to local codes. If you feel you do not have the experience necessary to do this, please have your fixture installed by a qualified, licensed electrician.

Make sure to note the maximum recommended wattage for your light fixture.
DO NOT EXCEED THE RECOMMENDED WATTAGE:

DVP44138 - 1 x 24W AC LED
DVP44148 - 1 x 42W AC LED

Cleaning
We recommend that you use a mild detergent, such as dish washing soap, and warm water to clean the glass and metal surfaces. After cleaning, make sure to dry the fixture completely because moisture will corrode the satin finish. Use a damp soft cloth to wipe off dust. DO NOT use abrasive pads or cleaning materials.

During installation, some fixtures may require subtle adjustments in order for the fixture to look as intended.

Tools

Phillips Head Screwdriver



If you have and questions,comments, or concerns contact us at customerservice@dvi.lighting

DVI Lighting
120 Great Gulf Drive, Concord
Ontario, L4K 5W1 Canada
T: 1 855 384 5483
F: 1 855 384 8435

C INTERTEK ETL LISTED US

5YR warranty
Garantie de 5ans



RENOVATING YOUR HOME?

Snap a photo of your fixture in your home and tag us on our social media for your chance to be featured!



A. Connect the copper ground wire to ground wire - If you only have two wires coming from the electrical box, connect the fixture's copper wire to the green ground screw on the mounting plate.
B. Connect the white fixture wire to white supply wire.
C. Connect the black fixture wire to black supply wire.



These instructions are property of DVI Lighting. Do not copy or reproduce.

DVI®
WWW.DVI.LIGHTING

DAWSON

SET COLOUR TEMPERATURE

Please keep this document for future reference

1



2



These instructions are property of DVI Lighting. Do not copy or reproduce.

DVI®
WWW.DVI.LIGHTING

DAWSON

LED MODULE REPLACEMENT INSTRUCTIONS

Please keep this document for future reference

4



5



DVP44138
KIT24W5CCT

DVP44148
KIT42W5CCT

6



7



8



Repeat steps 1-3 to reinstall the luminaire.

These instructions are property of DVI Lighting. Do not copy or reproduce.

DVI®

WWW.DVI.LIGHTING

DAWSON

PLAN DE MONTAGE

DVP44138
DVP44148

Avertissement
Risque d'incendie et de choc électrique. Ce produit doit être installé par un electricien qualifié et certifié. Votre filerie doit être conforme aux codes locaux et nationaux. Si vous n'avez que deux fils dans votre boite electrique, vissez le fil en cuivre sur la barre transversals de l'appareil.

NE PAS EXCÉDER LE WATTAGE RECOMMANDÉ:

DVP44138 - 1 x 24W AC DEL
DVP44148 - 1 x 42W AC DEL

Nettoyage
Épousseter, pour nettoyer le verre à fond, laver à la main avec un savon doux et assécher immédiatement pour retenir le fini satiné. N'utilisez pas de produits abrasifs ou chimiques.

Instruments

Tournevis Phillips

Pour toutes questions ou commentaires veuillez nous contacter au customer.service@dvi.lighting

DVI Lighting
120 Great Gulf Drive, Concord
Ontario, L4K 5W1 Canada
T: 1 855 384 5483
F: 1 855 384 8435

5YR warranty
Garantie de 5ans



FIER DE VOS RÉNOVATIONS?
Prenez une photo de votre pièce avec ce luminaire et identifiez-nous pour courrir la chance qu'on la partage!



A. Fixez le fil de terre en cuivre à la mise à la terre. S'il n'y a que deux fils qui sortent de la boîte de sortie électrique, fixez le fil en cuivre de l'appareil d'éclairage à la vis de terre en vert de la barre transversale.
B. Brancher le fil blanc au fil à nervures(neutre) du luminaire.
C. Brancher le fil noir au fil noir du luminaire.



Ces instructions sont la propriété de DVI éclairage. Ne pas copier ou de reproduire.

DVI®
WWW.DVI.LIGHTING

DAWSON

TEMPÉRATURE DE COULEUR

Veuillez conservez ce document pour référence ultérieure

1



2



Ces instructions sont la propriété de DVI éclairage. Ne pas copier ou de reproduire.

DVI®
WWW.DVI.LIGHTING

DAWSON

INSTRUCTIONS DE REMPLACEMENT DU MODULE DEL

Veuillez conservez ce document pour référence ultérieure

DVP44138
KIT24W5CCT

DVP44148
KIT42W5CCT

4



5



6



7



8



Répétez les étapes 1 à 3 pour réinstaller le luminaire.

Ces instructions sont la propriété de DVI éclairage. Ne pas copier ou de reproduire.